

home

searching ▾

patents ▾

documents ▾

toc journal watch ▾

Format Examples

US Patent

US6024053 or 6024053

US Design Patent

D0318249

US Plant Patents

PP8901

US Reissue

RE35312

US SIR

H1523

US Patent Applications

20020012233

World Patents

WO04001234 or WO2004012345

European

EP1067252

Great Britain


GB2018332

German

DE29980239

Nerac Document Number (NDN)

 certain NDN numbers can be used
 for patents

[view examples](#)


Patent Ordering



Enter Patent Type and Number: optional reference note



☐ Add patent to cart automatically. If you
 uncheck this box then you must *click on*
 Publication number and view abstract to Add to
 Cart.

6 Patent(s) in Cart

Patent Abstract



GER 1999-06-24 19757197 **Manufacture procedures
 for micro-mechanical appliance**
**ANNOTATED TITLE- Herstellungsverfahren foOr
 mikromechanische Vorrichtung**

INVENTOR(S)- Funk, Karsten 70195 Stuttgart DE

INVENTOR(S)- Frey, Wilhelm, Dr. 70469 Stuttgart DE

APPLICANT(S)- Robert Bosch GmbH 70469 Stuttgart
 DE

PATENT NUMBER- 19757197/DE-A1

PATENT APPLICATION NUMBER- 19757197

DATE FILED- 1997-12-22

DOCUMENT TYPE- A1, DOCUMENT LAID OPEN (FIRST
 PUBLICATION)

PUBLICATION DATE- 1999-06-24

INTERNATIONAL PATENT CLASS- G02B02608;
 C23F00104; H01L04900; G02B02608M4B; B81B00300M2D

PATENT APPLICATION PRIORITY- 19757197, A

PRIORITY COUNTRY CODE- DE, Germany, Ged. Rep. of

PRIORITY DATE- 1997-12-22

FILING LANGUAGE- German


LANGUAGE- German NDN- 203-0421-7037-3

The invention creates a manufacture procedure for a micro-
 mechanical appliance, especially for a micro-mechanical
 Schwingungsspiegelvorrichtung, with the steps,: With what the
 second layer (20) lies between the first and the third layer
 (10, 30) prepares a three-layered structure (10, 20, 30)

with a first layer (10), a second layer (20) and a third layer (30),; Durchtoetzen of the first layer (10) up to the second layer (20) to generating an on the second layer (20) of lying island area (40), that over one or several connection bridges (50), with which is surrounding area (60) of the first layer (10) interconnected the island area, and Durchtoetzen of an area (70, 80) the third layer (30) up to the second layer (20) and removing of an area (75, 85) the second layer (20) under the island area (40), so, that the island area (40) can execute movements, preferably torsion vibrations, about the one or them/her/it several connection bridge (50), the such an amplitude shows, that a part of the island area (40) in-sticks out the third layer (30) into the durchgehoetzten area (70, 80).

EXEMPLARY CLAIMS- 1. Manufacturing process for a micromechanical forwards-direction, in particular for a micromechanical swing- mirror device, with the steps: Makes available to a dreischichtigen structure (10, 20, 30) with a first layer (10), a second layer (20) and a third layer (30), whereby the second layer (20) lies between first and the third layer (10, 30); Durchtoetzen of the first layer (10) up to the second layer (20) for producing one on the second layer (of 20) lie-genden island range (40), which more ber one or more-connection bars (50) with the island range (40) surrounding range (60) of the first layer (10) is connected; and Durchtoetzen of a range (70, 80) of the third layer (30) up to the second layer (20) and removing a range (75, 85) of the second layer (20) under the island range (40) in such a manner, since the island range (40) can ausfhren around or several connecting posts (50) movements, preferably torsion vibrations, which exhibit such an amplitude, there a part of the island range (40) into the durchgetzten range (70, 80) of the third layer (30) projects. 2. Procedure according to requirement 1, by it marked, there zunchst the Durchtoetzen of the range (70) of the third layer (30), afterwards the Durchtoetzen of the first layer (10) and afterwards removing the range (75) of the second layer (20) is durchgefhr. 3. Procedure according to requirement 2, thereby is marked, there the Durchtoetzen of the range (70) of the third layer (30) is durchgefhr by an anisotropic Rckseitentzung. 4. Procedure according to requirement 1, 2 or 3, thus gekenn -, there the Durchtoetzen of the first layer (10) draws by a Trockentzung is durchgefhr. 5. Procedure according to requirement 1, by it marked, there zunchst the Durchtoetzen of the first layer (10) and afterwards removing the range (85) of the second layer (20) and the Durchtoetzen of the range (80) of the third layer (30) is durchgefhr. 6. Procedure according to requirement 5, thereby is marked, there the Durchtoetzen of the range (80)

NO-DESCRIPTORS

 **proceed to checkout**

Nerac, Inc. One Technology Drive . Tolland, CT
Phone (860) 872-7000 Fax (860) 875-1749

©1995-2003 All Rights Reserved . [Privacy Statement](#) . [Report a Problem](#)